

Pylontech PowerCube M1C



Kapacita (kWh)	85,3	90,0	94,8	99,5	104,3	109,0	113,8	118,5
Počet modulů	18	19	20	21	22	23	24	25
Bateriový střídač								
SMA SI50-20	✓	✓	✓	✓	✓	✓	✓	✓
Pramac PBI 50/88K	✗	✗	✗	✓	✓	✓	✓	✗
Kaco gridsave 92.0 TL3-S	✗	✗	✗	✗	✗	✗	✗	✓

Hybridní střídač								
GoodWe 40/50 ET	✓	✓	✓	✓	✓	✗	✗	✗

Další informace

Jsou k dispozici dvě verze bateriového racku:

- Menší verze má 24 pozice = maximum 23 modulů + 1 BMS
- Větší verze má 26 pozice = maximum 25 modulů + 1 BMS

Paralelní zapojení racků je možné s dalším příslušenstvím.

Kompatibilita založena na rozsahu napětí, listech kompatibilit výrobců a testováním v provozu.

Pylontech PowerCube M1C



Capacity (kWh)	85,3	90,0	94,8	99,5	104,3	109,0	113,8	118,5
# of modules	18	19	20	21	22	23	24	25
Battery inverter								
SMA SI50-20	✓	✓	✓	✓	✓	✓	✓	✓
Pramac PBI 50/88K	✗	✗	✗	✓	✓	✓	✓	✗
Kaco gridsave 92.0 TL3-S	✗	✗	✗	✗	✗	✗	✗	✓

Hybrid inverter								
GoodWe 40/50 ET	✓	✓	✓	✓	✓	✗	✗	✗

Additional info

Two battery racks for M1C are available:

- Smaller version has 24 positions = maximum 23 modules + 1 BMS
- Bigger version has 26 positions = maximum 25 modules + 1 BMS

Paralleling of battery racks is possible.

Compatibility based on voltage ranges of inverters, compatibility list of manufacturers and filed-testing.