

High Voltage Lithium-Ion Phosphate Battery storage system -Powercube M1C Battery Module: H32148-C



Module **H32148 -C**

Basic Parameters	
Capacity(kWh)	4.74
Nominal Voltage(Vdc)	32
Nominal Capacity(AH)	148
Voltage Range(Vdc)	30~36
Depth of Discharge	90%
Dimension(W*D*H,mm)	330*628*150.5
Communication	RS485/CAN
Protection Class	IP20
Weight(kg)	48
Operation Life	10+ years
Operation Temperature	0~50°C
Storage Temperature	-20~60°C
Product Certificate	UN38.3/ UL9540A



Main Controller : SC1000-200

Module

SC1000-200L-C

Basic Parameters

Related Product PowerCube-M1 C

AC Supply 230Vac/50Hz/1.3A

System Operation Voltage (Vdc) 0~1000

Operation Current (Max.) (A) 148

Self-consumption Power-Relay Off (W) 12

Self-consumption Power-Relay On (W) 19

Dimension (W*D*H, mm) 330×628×150.5

Communication MODBUS RTU/CAN /LAN

Protection Class IP20

Weight(kg) 13

Operation Life 15+

Operation Temperature -20~65

Storage Temperature -40~80

BMS Function

Protection and Alarm

- Charge/Discharge End
- Charge Over Voltage
- Charge/Discharge Over Current
- High/Low Temperature
- Operation Record
- Administrator Monitor: Current, Voltage, Temperature, SOC&SOH.

Management and Monitor

- Cells Balance
- Intelligent Charge Model
- Capacity Retention Calculate
- Isolation and Protection
- Alarm and Protection


Main Controller : SC1000-200J
Module
SC1000-200J-C
Basic Parameters

Related Product	PowerCube-M1C
-----------------	---------------

AC Supply	---
-----------	-----

System Operation Voltage (Vdc)	0~1000
--------------------------------	--------

Operation Current (Max.) (A)	148
------------------------------	-----

Self-consumption Power-Relay Off (W)	6
--------------------------------------	---

Self-consumption Power-Relay On (W)	15
-------------------------------------	----

Dimension (W*D*H, mm)	330×628×150.5
-----------------------	---------------

Communication	MODBUS RTU/CAN /LAN
---------------	---------------------

Protection Class	IP20
------------------	------

Weight(kg)	13
------------	----

Operation Life	15+
----------------	-----

Operation Temperature	-20~65
-----------------------	--------

Storage Temperature	-40~80
---------------------	--------

BMS Function
Protection and Alarm

- Charge/Discharge End
- Charge Over Voltage
- Charge/Discharge Over Current
- High/Low Temperature
- Operation Record
- Administrator Monitor: Current, Voltage, Temperature, SOC&SOH.

Management and Monitor

- Cells Balance
- Intelligent Charge Model
- Capacity Retention Calculate
- Isolation and Protection
- Alarm and Protection

Powercube M1



Module	PowerCube-M1C
Basic Parameters	
Battery System Capacity (kWh)	4.74*n
Battery System Voltage (Vdc)	32*n
Battery System Capacity (AH)	148
Battery Module	H32148-C
Battery Module Capacity (kWh)	4.74
Battery Modules Qty. (Optional)	1~ 23
Battery System Charge Upper-Voltage(Vdc)	36*n
Battery System Standard Operation Current(A)	29.6
Battery System Normal Operation Current(A)	74
Battery System Max. Operation Current(A)	148
Battery System Discharge lower-Voltage(Vdc)	27*n
Efficiency	95%
Depth of Discharge	95%
Dimension(W*D*H, mm)	815*659*2130
Communication	RS485/CAN/Ethernet
Weight (kg)	120kg+47*n
Operation Life	10+Years
Operation Temperature	10~40°C
Storage Temperature	-20~60°C
Humidity	5%~95%
Altitude (m)	<4000
Product Certificate	IEC62619/IEC63056/UL1973/UL954 0A/VDE2510-50/CE/UN38.3